

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **05220712 A**

(43) Date of publication of application: **31.08.93**

(51) Int. Cl.

B27K 3/15
B27K 3/50

(21) Application number: **04056906**

(22) Date of filing: **06.02.92**

(71) Applicant:

**MOKUZAI SEINOU KOJO GIJUTSU
KENKYU KUMIAI**

(72) Inventor:

**MAKI HIROHISA
SAMEZAWA HIROSHI
KUZE MASAYOSHI**

**(54) TREATING AGENT AND TREATING METHOD FOR
IMPROVING DIMENSIONAL STABILITY OF WOOD**

(57) Abstract:

PURPOSE: To provide low cost and safe treating agent and treating method, with which the dimensional stability of wood is settled and the wood can be effectively modified without impairing the characteristics of the wood.

CONSTITUTION: The treating agent includes at least one monomer selected from the group consisting of polyethylene glycol monoacrylate and polyethylene glycol monomethacrylate, at least one crosslinker selected from

the group consisting of polyethylene glycol diacrylate, polyethylene glycol dimethacrylate and methylene bisacryl amide and polymerization catalyst and can be used in the form of water solution. By adhering the treating agent to wood through polymeric fixation, the dimensional stability can be improved in low degree of impregnation and with very good durability. In addition, the wood treated by the above-mentioned method can be applied with normal wood coating and the crack and separation of coating film are a few, even when the coated wood is used outdoors.

COPYRIGHT: (C)1993,JPO&Japio

AN - 1993-308622 [39]

A - [001] 017 034 04& 04- 06- 074 076 077 08& 081 084 085 086 09& 09- 10&
10- 130 133 134 15& 17& 18& 18- 19& 19- 20& 264 265 266 27& 271 273
28& 398 431 438 477 546 57- 58& 59& 679 690 691 726

- [002] 017 028 147 198 226 231 239 336 575 58- 583 589 688 720 723

AP - JP19920056906 19920206

CPY - MOKU-N

DC - A14 A25 A97 F09 P63

DR - 0426-U 0743-U 1208-U 1737-U 5020-U 5329-U

FS - CPI;GMP

IC - B27K3/15 ; B27K3/50

KS - 0013 0030 0034 0040 0043 0046 0049 0052 0157 0160 0163 0166 0169 0206
0230 0231 0495 0496 0502 0503 0593 0594 0600 0601 1172 1173 1214 1215
1279 1588 1594 1999 2021 2024 2025 2034 2066 2122 2123 2432 2509 2585
3152 3204 3205 3206 3268

MC - A04-B A04-B09 A04-F06A A08-C01 A10-B01 A10-E07B A11-B05 A11-B05C
A12-B09 F05-B

PA - (MOKU-N) MOKUZAI SEINO KOJO GIJUTSU KENKYU KUMIAI

PN - JP5220712 A 19930831 DW199339 B27K3/15 004pp

PR - JP19920056906 19920206

XA - C1993-137021

XIC - B27K-003/15 ; B27K-003/50

XP - N1993-237753

AB - J05220712 Material is treated by (a) sticking a treating compsn. comprising (A) polyethylene glycol monoacrylate and/or polyethylene glycol monomethacrylate, (B) a crosslinking agent of polyethylene glycol diacrylate, polyethylene glycol dimethacrylate and/or methylene bis-acrylamide and (C) a polymerisation catalyst; and (b) polymerising the compsn. to fix the polymer to the wood material.

- Pref. (A) has an average mol. wt. of up to 4000 and pref. of 350-2000. (B) has an average mol. wt. of up to 2000 and pref. of 350-1000 and is used in a wt. ratio of (A)/(B) of 70:30-98:2. (C) is, e.g., an oxidising agent (e.g., Na-, K- or NH₄-persulphate), a combination of an oxidising agent and a reducing agent (e.g., diethanolamine, triethanolamine, hydrazine or morpholine) or an azo cpd. (e.g., 2,2'-azobis-isobutyronitrile).

- ADVANTAGE - Improves durability and dimensional stability at a low impregnation degree. The treating agent is used as its aq. soln. to provide high hygienic safety. The treated wood can be painted with a conventional wood paint to provide low cracking and low peeling of coated paint film and long durability. (Dwg.0/0)

IW - TREAT METHOD ENHANCE DIMENSION STABILISED WOOD MATERIAL COMPRISE STICK COMPOSITION COMPRISE POLYETHYLENE POLYGLYCOL MONO METHO ACRYLATE CROSSLINK AGENT POLYMERISE CATALYST

IKW - TREAT METHOD ENHANCE DIMENSION STABILISED WOOD MATERIAL COMPRISE STICK COMPOSITION COMPRISE POLYETHYLENE POLYGLYCOL MONO METHO ACRYLATE CROSSLINK AGENT POLYMERISE CATALYST

NC - 001

OPD - 1992-02-06

ORD - 1993-08-31

PAW - (MOKU-N) MOKUZAI SEINO KOJO GIJUTSU KENKYU KUMIAI

**TI - Treating method for enhancing dimensional stability of wood material -
comprises sticking with compsn. comprising polyethylene glycol]
mono(meth)acrylate, crosslinking agent, and polymerisation catalyst**